

Manual valves

Series 500



The manual valves, 504-505 series, are produced in Italy according to the reference ISO norms as warranty of high quality level.

Technical sheet


CONNECTING TUBES		Normally not applied directly to pipes, however defined according to the applications
TEMPERATURE AND PRESSURE	Working temperature	from -20° to +70° °C
	Max. working pressure	10 bar
THREAD TYPE		BSP parallel UNI-ISO 228
MATERIALS	Series 505 body	Brass UNI EN 12165 CW617N
	Series 504 body Series 504-505 slider	Anodized aluminum
	Seals gasket	NBR 70 DWGV-EN549 UL157

ART. **504**

Hand slide valve



COD.	A	B	C			
50418	G1/8	25	40	14	10	42,00
50414	G1/4	30	46	17	10	74,00
50438	G3/8	35	52	21	10	122,00
50412	G1/2	40	62	26	10	170,00



ART. **505**

Brass hand slide valve



COD.	A	B	C			
505M5	M5	14	30,5	10	10	11,80
50518	G1/8	25	48	14	10	50,50
50514	G1/4	30	58	19	10	95,50
50538	G3/8	35	70	22	10	154,00
50512	G1/2	40	75	27	10	210,00
50534	G3/4	50	83	32	10	187,00

